Wisco Moran Drilling Company



DRAWWORKS

Cabot 750-2042, 750 HP mounted on Cabot back-in carrier Powered by two Detroit Diesel 60 series engines, 900 continuous hp 1-1/8" drill line Parkersburg 22" hydromatic brake

MAST

Cabot 112' telescoping 300,000 # static hook load Six sheave crown block

SUBSTRUCTURE

Cabot 15' telescoping 300,000 # rotary capacity 13'-2" clear height

PUMPS

One Bomco F-1000, 1,000 hp triplex One Weatherford MP-10, 1,000 hp triplex Each independently powered by Caterpillar D-3508 diesel engines

MUD TANKS

Two Tanks, 850 bbl capacity

SOLIDS EQUIPMENT

Dual Derrick Hyperpool linear motion shale shakers Derrick vacuum degasser Derrick 2 cone desander Derrick 12 cone desilter

RIG NO. 10- INVENTORY OF EQUIPMENT

ROTARY

Bomco 17-1/2"

TRAVELING EQUIPMENT

Brewster block BJ 150 ton hook Brewster 200 ton swivel

ELECTRICAL SYSTEM

Two 350 KW gensets powered by Caterpillar C-15 engines

BLOWOUT PREVENTERS

Shaffer LWS 11" 5,000 psi double ram

CHOKE MANIFOLD

5,000 psi choke manifold

ACCUMULATOR

Koomey 5 station with remote panel

AUXILIARY EQUIPMENT

Foster Kelly spinner Ingersoll Rand air hoist

DRILL PIPE

Per Contract

DRILL COLLARS

Per Contract