



RIG NO. 6- INVENTORY OF EQUIPMENT



WELLCONTROL: 13-5/8" 5,000 psi annular
13-5/8" 10,000 psi double ram 210 Gallon
10,000 psi Choke Manifold

ACCUMULATOR: NL Shaffer 7 Station with Remote Panel

MUDSYSTEM: TWO (2) Two Tanks, 800 bbl capacity

SHALE SHAKERS-TWO (2) Two Brandt King Cobra Dual Motion shale shakers Atmospheric Degasser

GENERATORS: Four (4) Caterpillar 3512 engines SCR/MCC power control house 4 x 4 with Top Drive Feeder

SCR HOUSE: Omron 4x4

BLOCK/HOOK: Ideco 480 ton block

ROTARYTABLE: Ideco 27-1/2"

WATER TANK: 500 BBL

FUEL TANK: 10,000 Gallon

DRILLERS DOGHOUSE:

AUXILIARY EQUIPMENT: Electronic drilling recorder Ingersoll Rand air hoists Iron Roughneck Automatic Catwalk

INSTRUMENTATION: WEIGHT INDICATOR, W/TONG LINE PULL, PUMP PRESSURE & ROTARY TORQUE GAUGES, TYPE "D" 5,000 PSI MUD PRESSURE GAUGE

DRILL PIPE: 5" S135 19.50 #

DRILL COLLARS: Per Contract

WELL SITE TRAILERS: RIG MANAGER TRAILER 54' X 12'6" X 11'8", CREW CHANGE HOUSE

DRAWWORKS: National 110 UE, 1500hp
Baylor 6032 Aux Brake 1-3/8" drill line

ENGINES: Powered by Two (2) 800 HP GE 752 traction motors

MAST: Superior 142'
768,000 # static hook load

SUBSTRUCTURE: Box on Box 25' x 34' x 50'
25' KB height
High Density Walking System - 135'

AC TOP DRIVE: Canrig Model 1250AC, 500-ton
51,000 Ft/lbs of Continuous Torque

MUD PUMPS: Three (3) Bomco FB-1600, 1600 hp triplex
Powered by two 800HP traction motors
Rated at 7,500 psi